



**华特粉体**  
HUA TE POWDER



**中国粉体科技创新领导品牌**

Perfect match between drive station and energy consumption of grinding, energy saving to the fullest extent possible.

Forming a closed system with classifier, with negative pressure transport, without powder pollution.

### 应用范围(Application):

Soft material: calcite, marble, limestone, barite, gypsum, slag etc.

Hard material: quartz, felspa, carbonundum, corundum, fine cement etc.

### 技术参数(Technical Parameter):

| Item                            | * +                  |            |                                      |            |                                |
|---------------------------------|----------------------|------------|--------------------------------------|------------|--------------------------------|
| 1250 ( )                        | 0.8                  | 1          | 1.5                                  | 2          | 3                              |
|                                 | 1500                 | 2200       | 3300                                 | 4000       | 7500                           |
|                                 | 1400                 | 1900       | 2900                                 | 3500       | 6500                           |
|                                 | 1000                 | 1400       | 2200                                 | 2700       | 4400                           |
|                                 | 450                  | 580        | 880                                  | 1100       | 1760                           |
|                                 | § 1.5X5              | § 1.83X4.5 | § 1.83X6                             | § 2.2X4    | § 2.2X6<br>, § 2.4X6 § 2.6X6   |
|                                 | 110                  | 160        | 220                                  | 250        | 560                            |
|                                 | HFW500 or<br>HFW3315 | HFW4315    | HFW4400 or<br>HFW6315 or<br>2HFW3315 | HFW3500    | HFW4500 or<br>HFW6400 or<br>2H |
|                                 | % 300                | % 380      | % 550                                | or2HFW4315 | % 1130                         |
| ! Fliter area' m <sup>2</sup> # | 120                  | 160        | 250                                  | % 700      | 500                            |
| & Thickness of dust             |                      |            |                                      |            |                                |

1 1250

(All of the parameters above are according to 1250 mesh GCC)

2

(As different material from different places, the parameter is just for your reference)